

BRM Mobile Jaw Crusher Range

BRM Mobile Jaw Crusher Range

The **BRM** range of new Mobile Jaw Crushers combines outstanding capacity, upto 600 tph, with excellent reliability by using tried and tested electric & hydraulic drives. This combination ensures best possible value for contractors and operators. An option of CATERPILLAR diesel engine driven crushers is also available.

The **BRM** range is designed to fulfil various crushing needs, from hard rock quarrying to recycling and demolition. Easily towed to site, they are quickly 'up and running' producing your crushed aggregate.

BRM RANGE

Model	Jaw
Opening	Capacity

BRM 90-60	36" x 24" / 915 x 610 mm	From 60 to 210 tonnes per hour
-----------	-----------------------------	-----------------------------------

BRM 110-75	42" x 30" / 1066 x 762 mm	From 130 to 400 tonnes per hour
------------	------------------------------	------------------------------------

BRM 120-110	48" x 42" / 1219 x 1066 mm	From 180 to 625 tonnes per hour
-------------	-------------------------------	------------------------------------

- **Heavy duty** single toggle jaw crushers.
- **Heavy duty feed hopper**—folds for transport.
- **Heavy duty**

Office Address: Moorside, Sutton Road, Thirsk, North Yorkshire, YO7 1DL
Yard Address: Sheepbridge Lane, Chesterfield, Industrial Estate, Chesterfield, Derbyshire, S41 9RX

Tel: +44(0) 1845 869 347 / Email: sales@pqs.uk.net

2013 Copyright Port & Quarry Supplies Limited.

- Choice of three **jaw crushers** from 915 x 610 mm to 1219 x 1066 mm.
- **Electric** drives to crusher, feeder and conveyors.
- Optional **CATERPILLAR** diesel drive
- **Hydraulic** power for folding hopper and conveyor.
- Discharge **conveyor**.
- Twin or triple axle **mobile** road towable chassis with support legs.

CAPACITY

Model	Jaw Opening	
	Min. Setting	Max. Capacity
BRM 90-60	915 x 610 mm	60 to 80 tph
	63.5 mm	152 to 210 tph
BRM 110-75	1066 x 762 mm	310 to 400 tph
	102 mm	130 to 150 tph
	304 mm	310 to 400 tph
BRM 120-110	1219 x 1066 mm	180 to 200 tph
	102 mm	304 to 625 tph
	550 mm	550 to 625 tph

DIMENSIONS

Model	Length	
	Width	Weight
BRM 90-60	11	
510		2
500	4	
100		35
Tonnes		
BRM 110-75	12	
300		2
500	4	
390		58
Tonnes		
BRM 120-110	14	
000		2
600	4	
750		75
Tonnes		