

BRM Conveyor Mobile Radial



Mobile, radial, troughed belt conveyors, fitted with 3 ply / 30" 750 mm wide conveyor belting with a vulcanised joint (chevron belt available as an option). Feed boot (with extended sides as standard), support pivot and fully guarded

- Available in lengths 40 ft. / 12 m, 50 ft. / 15 m and 60 ft. / 18 m centres
- Hydraulic drive as standard (to be driven off another machine)
- Electric or diesel / hydraulic drive available as options
- Hydraulic raise and lower mechanism with galvanised pins and coupling blocks
- Single axle / single wheel can be converted to radial turning
- Remote greasing points all to one point, for ease of servicing
- All conveyors can be containerised for shipping
- All conveyors will not exceed 40 feet long when folded over
- Quality and value. Made in the UK

STOCKPILE CAPACITY

Belt inclination 20 degrees and a radial angle of 60 degrees (although 140 to 160 degrees may be possible)

Conveyor Length	Height under head	Capacity Static	Capacity Radial 60 Degrees
40 Ft / 12 M	21 ft / 6.5 m	350 cubic metres	1000 cubic metres
50 Ft / 15 M	25 ft / 7.7 m	650 cubic metres	1900 cubic metres
60 Ft / 18 M	30 ft / 9.2 m	800 cubic metres	3000 cubic metres



BRM Conveyor

Port & Quarry Supplies Limited

Telephone 01530 414 358